

**DESCRIPTION**

Total thickness	EN ISO 24346	mm	1.6 / 2.0 / 2.5 / 3.0 / 3.5	2
Weight	EN ISO 23997	g/sq.m	3050 / 3920 / 4860 / 6000 / 6500	3920
Tile size	EN ISO 24342	mm	300 x 300	600 x 600
Approx. Number of tiles per package	-	-	90 / 70 / 56 / 46 / 44	22
Approx. area coverage per box	-	m <sup>2</sup>	8.10 / 6.30 / 5.04 / 4.14 / 3.96	7.92
Approx. weight per box	-	kg	25	31

**CLASSIFICATION**

Norm / Product specification	-	-	EN ISO 10581	
European classification	EN ISO 10874	class	34 – 43	
Fire rating	EN 13 501-1	Class	Bfl-s1	
Slip resistance wet	DIN 51 130	Class	R9	
Electrical resistance	EN 1081	Ohm	< 10 <sup>8</sup>	
Static electrical propensity	EN 1815	kV	< 2	

**PERFORMANCE**

Wear resistance	EN 660.2	-	≤ 4.0	
Wear group	EN 654	class	P	
Dimensional stability (requirement)	EN ISO 23999	%	≤ 0,25	
Residual indentation (norm)	EN ISO 24343-1	mm	≈ 0.03	
Thermal conductivity	EN ISO 10456	W/(m.K)	0,25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	
Surface treatment	-	-	PU	
Chemical products resistance	EN ISO 26987	class	OK	
Anti-bacterial & fungicidal treatment	EN ISO 846	-	OK	