



TECHNICAL CHARACTERISTICS

Vinyl planks



DESCRIPTION

Total thickness	EN 428	mm	1.80
Thickness of the wear layer	EN 429	mm	0.08
Weight / Mass per unit area	EN 430	g/sqm	3530
Dimensions	EN 427	cm	91.4 x 15.2
Tile per box	-	tiles	16
Area per box	-	sqm	2.2

CLASSIFICATION

Norm / Product specification	-	EN 649	EN 649
European classification	EN 649	class	22
Fire rating - Classification	NF EN 13501-1	class	Bfl S1
Wear Group	EN 649	group	T
VOC rating (French norm)	-	-	A+
VOC rate 28 days	-	µg/m³	< 100

PERFORMANCES

Sound insulation	EN ISO 717/2	dB	3
Room impact noise	NF S 31074	class	C
Dimensional stability after exposure to heat	EN 434	%	< 0.25
Residual Indentation	EN 433	mm	0.05
Colour fastness	EN 20 105 - B02	degree	≥ 6
Garantee residential use	-	year	5

CE MARKING

CE	EN 14041			
-----------	----------	--	--	--

Areas of use: domestic



CLEANING & CARE

General – see page 257

To replace a tile or plank

- With a utility knife, pierce the tile or plank several times
- Heat it with a blow dryer to soften it
- Remove and replace it



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission

ENVIRONMENT

- 100% recyclable
- ISO 14001
- Soapy water cleaning