

DESCRIPTION

Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 24341	g/m ²	3135
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20

CLASSIFICATION

Norm / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	Bi-s1
Static electrical propensity	EN 1815	kV	< 2

PERFORMANCE

Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999	%	≤ 0.4
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Residual indentation (average measured value)	-	mm	~ 0.03
Castor chair test (type W)	ISO 4918	-	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	EVERCARE™
Chemical products resistance (1)	EN ISO 26987	class	OK
Antibacterial activity (E. coli – S. aureus – MRSA) (2)	ISO 22196	-	> 99 % inhibits growth

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®

- (1) Regarding the resistance to chemicals, please download the corresponding leaflet from our website
 (2) The implementation of an effective cleaning method is the best defence against infection